

Series ROS Multitone Audible Alarm



Description:

The Series ROS 32 Tone Audible Alarm can be used in applications such as security, general signaling and process alarms. The wide operating voltage and range of tones available makes this product adaptable to many uses.

Nominal Voltage:	9 - 28VDC
Current Consumption (tone dependant):	Max. 33mA @ 24VDC
Sound Output (tone dependant):	Between 88dB - 111dB
Alarm Tones:	32
IP Rating:	IP65 w/ deep base, IP54 w/ shallow base
Color:	Off White
Mounting:	Wall
Operating Temperature:	-25°C to 70°C
Volume Control:	0 to -20dB

Features:

- High Sound Output
- Low Current Consumption
- 32 Tones User Selectable
- Automatic Synchronization
- Volume Control
- Base Compatible with the Series CLR and FLS
- Weatherproof w/ deep case
- Indoor/Outdoor
- Two Style Alarm (1 programmable, 1 standard)

Specification and Ordering Information:

Model Number	Order Code	Description
ROS-DC	4064	Audible Alarm
DB	4090	Mounting Base



WE ENCOURAGE AND SUPPORT NICET CERTIFICATION
3 YEAR WARRANTY
ROS 32 08/08



NJ Location
273 Branchport Ave.
Long Branch, NJ 07740
P: 800-631-2148
F: 732-222-8707
www.coopernotification.com

FL Location
7565 Commerce Ct.
Sarasota, FL 34243
P: 941-487-2300
F: 941-487-2389

VA Location
P: 877-459-7726
F: 703-294-6560